

CERAMIC TRIMMER CAPACITOR – 5mm

◆ **Specifications**

- Operating Temperature Range : -30°C to +85°C
- Rated Working Voltage : 100VDC
- Withstanding Voltage : 400VDC
- Insulation Resistance : 10⁴ MΩ min.
- Rotation Torque : 35 ~ 200 g-cm
- Soldering Temperature : 260±5°C

◆ **Ratings**

PART NO.	MIN. CAP. (pF)	MAX. CAP. (pF)	TEMP. COEFF. PPM/°C	Q FACTOR @1MHz Cmax
CVNN05-030	1.3 max	3.0 ⁺¹⁰⁰ / ₋₀ %	NP0±250	>500
CVNN05-050	2.0 max	5.0 ⁺¹⁰⁰ / ₋₀ %	NP0±250	>500
CVNN05-100	3.0 max	10.0 ⁺¹⁰⁰ / ₋₀ %	N450±300	>500
CVNN05-200	4.2 max	20.0 ⁺¹⁰⁰ / ₋₀ %	N450±300	>500
CVNN05-300	5.2 max	30.0 ⁺¹⁰⁰ / ₋₀ %	N750±300	>500
CVNN05-400	6.8 max	40.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	>300
CVNN05-500	9.0 max	50.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	>200
CVNN05-600	11.0 max	60.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	>200
CVNN05-700	13.0 max	70.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	>200

◆ **Drawing**

NORMAL TYPE

